



Proven in Vietnam.
Built for America.

EB8


EB12

VinFast is more than a vehicle manufacturer. We bring proven electric transit experience to the United States, combining real-world bus operations with advanced technology to support cleaner, quieter and more efficient urban mobility for American transit agencies.



Reasons for

VINFAST eBus



**Fast
Charging**



**9-bath Electrophoretic
Anti-corrosion Coating**



**LFP
Battery**



**Competitive
Warranty**



**Low
TCO**

EB8

SPECIFICATION

Dimensions (L x W x H)	29.5 ft x 97.2 in x 128.0 in
Floor Height	≥ 15.7 in
GVW	≤ 28,991 lb
Battery Capacity	266.6 kWh
Maximum Power	340 kW (456 hp)
Peak Wheel Torque	≥ 15,415 lb-ft
Maximum Speed	65 mph
Driving Range	≥ 186.4 mi (SORT 2)
DC Fast Charging	1 x CCS1
Charge Time	< 45 min, 20–80%
Seating	Fixed 20 + Foldable 4 + 2
Wheelchair Bays	2
Kneeling	Standard

EB12

SPECIFICATION

Dimensions (L x W x H)	40 ft x 102 in x 130 in
Floor Height	≥ 15.7 in
GVW	≤ 43,000 lb
Battery Capacity	Base: 400 kWh • Optional: 528 kWh
Maximum Power	325 kW (436 hp), Dual Hub Motors
Peak Wheel Torque	≥ 16,522 lb-ft
Maximum Speed	65 mph
Driving Range	Base: ≥ 279.6 mi Optional: ≥ 341.8 mi (SORT 2)
DC Fast Charging	1 x CCS1
Charge Time	< 60 min (400 kWh) / < 80 min (528 kWh), 20–80%
Seating	2-Door: 33 Fixed + 6 Foldable Optional: ≥ 3-Door: 29 Fixed + 6 Foldable
Wheelchair Bays	2
Kneeling	Standard

*Range figures are based on SORT testing. Actual range may vary based on route, passenger load, driving conditions, climate, HVAC use, battery condition and other factors.

**Charging times are estimates from 20–80% state of charge and may vary based on charger capability, battery temperature, state of charge and environmental conditions.

***U.S. market specifications, features, configurations and availability are preliminary and subject to change prior to production and final certification.